

Fiber Optic LC-LC SM 9/125um 2mm Simplex Patch Cord

Features:

- Adopts high precision ceramic ferrule with good concentricity
- 100% inspected for optical characteristics & fiber end face finish
- Low insertion loss and return loss
- RoHS Compliant
- Telcordia GR-326, IEC, TIA/EIA Standard compliant



Application:

- Premise distribution networks
- Backbone networks
- Enterprise networks
- Telecom networks
- Data center
- FTTH

Specifications:

- Connector Type: LC/LC Simplex
- Optical Fiber: Single mode 9/125um G652D/G657A
- Cable type: LSZH/PVC, 2mm/3mm Simplex Zip cord
- Cable color, Length: Yellow, 1m – 150m

| General Specification | | |
|------------------------------|--|------------------|
| Connector | | |
| Type | LC | LC |
| Type of Polish | PC | PC |
| Body | Plastic | Plastic |
| Ferrule Material | Zirconia Ceramic | Zirconia Ceramic |
| Cable | | |
| Fiber | SM | |
| Type | 2mm /3mm Simplex Cable Yellow OFNR/LSZH jacketed | |
| Technical Specification | | |
| Cable | | |
| Insertion Loss | ≤ 0.3dB @ 1310 & 1550 nm Wavelength | |
| Return Loss | ≥45dB @ 1310 & 1550 nm Wavelength | |
| Operating Temperature | | |
| -20 ~ + 70 °C | | |