

Fiber Optic SC/APC-SC/APC SM 9/125um Duplex Patch Cord

Features:

- Adopts high precision ceramic ferrule with good concentricity
- 100% inspected for optical characteristics & fiber end face finish
- Low insertion loss and return loss
- RoHS Compliant
- Telcordia GR-326, IEC, TIA/EIA Standard compliant



Application:

- Premise distribution networks
- Backbone networks
- Enterprise networks
- Telecom networks
- Data center
- FTTH

Specifications:

- Connector Type: SC/APC/SC Duplex
- Optical Fiber: Single mode 9/125um G652D/G657A
- Cable type: LSZH/PVC, 2mm/3mm Duplex
- Cable color, Length: Yellow, 1m – 150m

General Specification		
Connector		
Type	SC/APC	SC/APC
Type of Polish	APC	APC
Body	Plastic	Plastic
Ferrule Material	Zirconia Ceramic	Zirconia Ceramic
Cable		
Fiber	SM	
Type	2mm/3mm Duplex Cable Yellow LSZH/OFNR jacketed	
Technical Specification		
Cable		
Insertion Loss	≤ 0.3dB @ 1310 & 1550 nm Wavelength	
Return Loss	≥60dB @ 1310 & 1550 nm Wavelength	
Operating Temperature		
-20 ~ + 70 °C		